



Australian Government

Security Construction
& Equipment Committee

CERTIFICATE OF APPROVAL – SL3



Bilock Exclusive 234B/45 padlock cylinder FA6536Q

Cylinder for Lockwood 234B/45 padlock

HAS BEEN APPROVED FOR
Keying systems – Security Level 3

CONDITIONS OF APPROVAL
No specific conditions of approval.

SUPPLIED BY

Australian Lock Company Pty Ltd
17 Doyle Avenue
Unanderra NSW 2526
T: 02 4260 5700
F: 02 4272 4527
E: customerservice@australianlock.com.au

APPROVAL GRANTED
9/02/2016



Chair
Security Construction and
Equipment Committee



SECURITY EQUIPMENT RATINGS

Security Level (SL) ratings applies a 'Good, Better, Best' philosophy to security products, SL4 being the most secure through to SL1 the least secure. The following includes a brief description of the risk profile associated with each Security Level:

SL4

High Risk - Attackers are expected to have a professional level of ability to resource and implement a physical/technical attack in detail. Attackers will have a high level of expertise and will be equipped with specialist tools and equipment. Products classified at this level will offer substantial resistance against a large range of specialist attack methods for extended periods.

SL3

Medium Risk - Attackers are expected to be highly capable using a comprehensive range of non-specialist tools and equipment at their disposal. Products classified at this level will offer a moderate resistance to a range of specialist attack methods for reasonable periods.

SL2

Low to Medium Risk - Attackers are expected to have a limited knowledge, and will have a general range of non-specialist tools and equipment. Products classified at this level will offer moderate resistance against non-specialist attacks for limited periods.

SL1

Low Risk - Attackers are expected to have little knowledge and only the most basic tools or equipment. Products classified at this level will offer minor resistance against any attacks for very short periods.